



**“Specialists in Expanded Metal Building Products”**

## **SELF-FURRED V GROOVE DIAMOND MESH LATH SPECIFICATION**



<b>Wt. Per Sq. Yd.</b>	<b>Sheet Size</b>	<b>Pcs. / Bdl</b>	<b>Yds. / Pallet</b>
2.50 lbs.	27" x 96"	10	500
3.40 lbs.	27" x 96"	10	500

25 bundles per pallet

**Niles Self-Furred V Groove Diamond Metal Lath provides a ¼", V groove, indentation running the length of metal lath furring the lath away from the sheathing base. There are 6 grooves on each sheet. It provides ample keying for scratch coat. This lath is produced from ASTM A653 standard specification for steel sheet, zinc-coated (galvanized) or zinc-iron alloy coated (galvannealed) by hot-dip process. Niles Self-Furred Diamond Metal Lath meets or exceeds the following ASTM Standards:**

ASTM C841 Standard specification for installation of interior lathing and furring  
ASTM C847 Standard specification for Metal Lath (2.5 and 3.4 only)

### **NILES BUILDING PRODUCTS CO.**

**Company Headquarters**  
1600 Hunter Street  
Niles, Oh 44446  
Phone: 800-323-3329  
Fax: 330-544-8868

[www.nilesbldg.com](http://www.nilesbldg.com)